

RF 100-300mm f/2.8L IS USM

TECHNICAL SPECIFICATIONS



Canon

RF 100-300mm f/2.8L IS USM

A flagship telephoto zoom lens



DELIVER BEAUTIFULLY BLURRED BACKGROUNDS

Express an artistic edge with smooth bokeh that beautifully draws your subject from the background. Experience great performance in low-light with a fast and wide f/2.8 aperture across the entire zoom range.



OUTSTANDING IMAGE QUALITY

RF 100-300mm f/2.8L IS USM is a culmination of cutting-edge optical design that delivers image quality that rivals prime lenses. Get the flexibility of a zoom lens that seamlessly covers the telephoto range and with an RF 1.4x or RF 2x extender can also achieve super telephoto reach.



FAST AND ACCURATE AUTOFOCUS

Stay discreet and in control thanks to rapid focusing from two high performance Nano USM motors combined with Dual Pixel CMOS autofocus. Lock onto fast-moving subjects like animals, sports and vehicles.



SHARP HANDHELD TELEPHOTO SHOOTING

The powerful 5.5 stops in-lens optical image stabilization (IS) or up to 6.0 stops co-ordinated control with a camera body with in-body IS, counters camera shake that may occur when using a large telephoto lens.



DURABLE AND TOUGH FOR THE RIGOURS OF PRO SHOOTING

The RF 100-300mm f/2.8L IS USM has been carefully crafted with dust and drip resistance construction and fluorine coating to repel oil and water. It has thermal barrier coating that reduces temperature increases caused by the sunlight. This L-series durability and robustness enables the lens to be used even in the harshest of environments.



RF 100-300mm f/2.8L IS USM | SPECIFICATIONS

RF 100-300mm f/2.8L IS USM	
Mount	RF
Focal Length	100-300mm
Maximum Aperture	f/2.8
Minimum Focusing Distance	1.8m
Maximum Magnification	0.06x (at 100mm) & 0.16x (at 300mm)
Lens Construction	23 elements in 18 groups
Filter Size Diameter	112mm
Aperture Blades	9
Image Stabilization	5.5 stops (In-lens Optical IS) 6.0 stops (with IBIS coordinated control)
Focus Drive System	2x Nano USMs
Dimensions	323.4mm (length), 89.2mm (diameter)
Weight	2,590g
Lens Hood	E-112 (included)
Lens Cap	ET-124 (included)
Lens Pouch	LS100-300 (included)

Canon

**www.canon.com.au
www.canon.co.nz**