

RF 600mm f/4 L IS USM

TECHNICAL SPECIFICATIONS



Canon

RF 600mm f/4 L IS USM

Professional Super-Telephoto Lens for the EOS R System



ENJOY HIGH RESOLUTION, HIGH CONTRAST AND HIGH-IMAGE QUALITY

The RF 600mm f/4 L IS USM inherits the superior optics of its EF counterpart and displays both high-image quality and light mobility. It delivers clear and sharp images, expressing the detail from the centre to the edge of the camera frame at maximum aperture.



NEVER MISS A MOMENT WITH HIGH-SPEED CONTINUOUS SHOOTING

The RF 600mm f/4 L IS USM supports the EOS R system's high-speed continuous shooting. Shoot up to 30 frames per second when using the EOS R3's electronic shutter. Capture the action with fast-moving subjects, such as sports or wild animals, without missing a beat.



REDUCE CAMERA SHAKE WITH HANDHELD SHOOTING

The lens' powerful 5.5 stop Image Stabilization (IS), when used with the EOS R or EOS R5, counters camera shake that may occur when using a large telephoto lens. It makes for stable shooting even when handheld. Select from three IS modes that is optimised to match your subject's movement.



MAKE SMOOTH ADJUSTMENTS WHEN RECORDING VIDEO

Aperture control during movie shooting can be set with a resolution of 1/8 step. The brightness can be changed smoothly, even when there is a sudden change in brightness, allowing for natural-looking footage.



RF 600mm f/4 L IS USM | SPECIFICATIONS

RF 600mm f/4 L IS USM	
Mount	RF
Focal Length	600mm
Maximum Aperture	f/4
Minimum Focusing Distance	4.2m
Maximum Magnification	0.15x
Lens Construction	17 elements in 13 groups
Filter Size Diameter	52mm
Aperture Blades	9 (Round)
Image Stabilization	Yes (5.5 stops when used with the EOS R or EOS R5)
Dimensions	Approx. 168mm x 472mm
Weight	Approx. 3,090g
Lens Hood	ET-160 (WIII) (Supplied)
Lens Cap	E-185C (Supplied)
Lens Pouch	LS600 (Supplied)
Drop-In Screw Filter Holder	52 (WIII) (Supplied)
Tripod Mount	(Supplied)

Canon

www.canon.com.au